## NewLook International, Inc. QuickEtch™



## Material Safety Data Sheet

Section 1

PRODUCT & COMPANY IDENTIFICATION

**Product Name:** QuickEtch™

Manufacturer's Name: NewLook International, Inc.

Manufacturer's Address: 1525 South Gladiola Street, Suite 8, Salt Lake City, UT 84104 Information Phone: NewLook International, Inc. 877.763.9566 or 801.886.9495

**Emergency Contact:** For Emergency information, contact Chemtel, Inc. at 800.255.3924, Outside the USA at 813.248.0585

#### Section 2

#### **HAZARDOUS INGREDIENTS**

DESIGNATIONS	PEL (PPM)	TLV (PPM)	EFFECTS (see reverse)	% IN PRODUCT
Organic Acidic Salt	NE	NE	IRR	30-50%

Other materials used in the product are not required to be listed or are below the requirements of 29 CFR 1910.1200, Subpart Z.

Hazard Rating (NFPA/HMIS): Rating Scale:

> Health = 2 0 = Minimal Fire = 0 1 = SlightReactivity = 2 2 = Moderate Special = 3 = Serious

4 = Severe

Personal Protection: С Chronic Hazards: No

Section 3

**HEALTH HAZARD DATA** 

ΝE Estimated PEL/TLV:

**Primary Routes of Entry:** Ingestion, Inhalation

**Acute Effects of Overexposure:** This product in concentrated form may be an eye and skin irritant. Contact with eye tissue may produce pain,

> watering, and/or burning sensation. Prolonged skin contact may irritate the skin. Inhalation of product mists may cause respiratory tract irritation. Ingestion of an excessive amount of the product may cause

complications.

**Chronic Effects of Overexposure:** There are no known effects from chronic exposure to this product.

SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use so long as prescribed safety precautions are practiced.

Section 4

FIRST AID MEASURES

Skin: Flush contaminated skin with plenty of water. Consult a physician if irritation develops.

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation develops, consult a physician. Eves:

Move exposed person to fresh air. If irritation persists, seek medical attention promptly. Inhalation:

Ingestion: If this product is swallowed, DO NOT induce vomiting. If victim is conscious, give plenty of water or milk to drink.

Seek medical attention immediately.

Section 5

SPECIAL PROTECTION INFORMATION

The use of rubber or plastic gloves is recommended if prolonged skin contact is expected. Wear a rubber apron to avoid **Protective Clothing:** 

splashing product on clothing.

©2011 NewLook International, Inc. - All Rights Reserved

www.getNewLook.com a 1525 South Gladiola Street, Suite 8, Salt Lake City, UT 84104 a 877.763.9566 a Office: 801.886.9495 a Fax:

204 226 0407

**Eye Protection:** Wear tight fitting safety glasses, especially if contact lenses are worn.

Respiratory Protection: Respiratory protection may be unnecessary since product does not give off significant quantities of vapor.

**Ventilation:** No extra measures are needed if ventilation is adequate.

Section 6 PHYSICAL DATA

Appearance and Odor: Clear, Amber gelled liquid

Boiling Point: >212°F Specific Gravity: 1.2

Vapor Pressure (MMHG): Not Determined

Evaporation Rate (Water = 1): < 1 Vapor Density (Air = 1): > 1

Solubility in Water: Complete, 100% pH: 1.0 to 2.0 VOC Content: None

Odor: Mild, Acidic Odor

Section 7

FIRE AND EXPLOSION DATA

Flash Point (°C):

Method Used:

Explosive Limits (Upper - % by Vol.):

PMCC

N/A

Explosive Limits (Lower - & by Vol.):

N/A

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures: When heated above the flash point, emits flammable vapors that, when mixed with air, can burn or be

explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

Unusual Fire and Explosion Hazards: Thermal decomposition of this product will produce carbon monoxide, carbon dioxide, and other toxic volatiles

Section 8

REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will not occur.

Materials to Avoid: Alkalis, Reactive Metals

Hazardous Decomposition Products: High temperatures may create oxides of carbon, nitrogen, and chlorine

Section 9

### SPILL AD DISPOSAL PROCEDURES

## Steps to be taken in case material is released or spilled:

Observe safety procedures in Section 5 during clean-up. Absorb spill on inert absorbent material. Pick up and place residue in a suitable waste container or, if permitted, flush to sewer. Thoroughly rinse spill area with water.

## **Waste Disposal Method:**

Liquid wastes are not permitted in landfills. This product is not considered a hazardous waste under RCA. Unusable liquid may be absorbed on an inert absorbent material, drummed, and taken to a chemical or industrial landfill. In some areas, disposal by flushing into a sanitary sewer with plenty of water may be permissible. Consult local, state, and federal agencies for proper disposal method in that area.

RCRA Hazardous Waste NOS.: None

Section 10

### SPECIAL PRECAUTIONS

## Precautions to be taken when Handling and Storing:

- Keep product out of eyes.
- Avoid prolonged contact with skin.
- Keep away from food and food products.
- Keep out of the reach of children.

Section 11

REGULATORY INFORMATION

DOT Proper Ship Name: Not Regulated

DOT Hazard Class: N/A
Dot Packing Group: N/A
DOT I.D. Number: N/A

DOT Label/Placard: N/A

NOTE: DOT information applies to larger package sizes of affected products. For some products, DOT may require alternate names and labeling in accordance with packaging group requirements.

**EPA TSCA Chemical Inventory:** All Ingredients are Listed EPA CWA 40CFR Part 117 Substance (RQ in a single container):

# Section 12 OTHER INFORMATION & LEGEND

**IMPORTANT:** The MSDS should be read before product disposal. Pass MSDS information to all persons who could be exposed to the product. The MSDS has been prepared according to OSHA Hazard Communication Standard (29 CFR 1910.1200). To the best of our knowledge, the information contained herein is accurate and based on sources believed to be reliable. However, since data, safety standards, and government regulations are subject to change, NewLook International, Inc. makes no warranty, either expressed or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. The data on this sheet is related only to this specific material. It may not be valid for this material if used in combination with any other materials. It is the end user's responsibility to determine suitability and completeness of this information with regards to a particular use. Additional information may be necessary or helpful for specific conditions and circumstances of use. Unknown hazards may exist and this material should be use with caution. NewLook International, Inc. assumes no legal responsibility for use or reliance upon this data.

PEL: Permissible Exposure Limit (OSHA)
TLV: Threshold Limit Value (ACGIH)